


Data Sheet



Type Number 4075
Designation IEC SR 44
System Silver oxide / Zinc /
 KOH - Electrolyte

Nominal Voltage 1,55 V
Typical Capacity C 145 mAh
 Load 5,6 kOhm, at 20°C down to 1.2 V

Weight (approx.) 2,4 g
Volume 0,51 ccm
Coding..... Manufacturing Quarter/Year by
 Letter Code

Temperature Ranges min max.
 Storage -10°C 65 °C
 Discharge -10°C 65°C

Dimensions min max.
 Diameter ... 11,25 11,6
 Height (A/B) 5 5,4

Segment Watch / High Drain

Main Applications Watch
 Photo
 Electronic

Typical Capacities (at 20°C)

Discharge Type	Load	End Voltage:	1.2 V
Continuous	5600 Ω	Time:	545 h
24h/d,7d/w		Capacity [mAh]:	145
Current [μA]:	275	Energy [MWh]:	215

All Data contained herein is for single cells

For battery applications, performance data may vary from single cell data, depending on specific battery configuration

VARTA Microbattery GmbH, Daimlerstr. 1, D-73479 Ellwangen/Jagst
 Tel.: (+49) 7961/921-0, Telefax: (+49) 7961/921-553

Subject to change without prior notice!
 Date of issue: 07.08.2003